



Sure Chemicals Ltd

A solution for every problem

Martindale Industrial Estate
Hawks Green Lane
Cannock
Staffs
WS11 7XN

Tel No: 01543 462000
Fax No: 01543 579311
Email: sales@surechemicals.co.uk
Web: www.surechemicals.co.uk

Technical Information

Product Code A006

ALLY – CLEAN 67

ALLY-CLEAN 67 is a specially formulated acid cleaner for the removal of scale and oxide from aluminium vehicle bodies, roller shutters and doors , aluminium wheels etc. May also be used for phosphating steel parts prior to painting.

ACIDIC CLEANER

REMOVES OXIDE FILM FROM ALUMINIUM

PREPARES SURFACE TO IMPROVE PAINT ADHESION

USE HOT OR COLD

ADDED WETTING AGENTS HELPS RINSING

DIRECTIONS FOR USE

Aluminium cleaning: Dilute 1 part ALLY-CLEAN 67 with up to 15 parts water. Apply to wetted surfaces, starting at lower edge and working upwards section at a time. Apply by brush or low pressure spray and hose or pressure wash off with water.

Derusting and phosphating: Dilute 1 part ALLY-CLEAN 67 with up to 3 parts water and immerse parts until rust is removed and steel surface is an even grey colour. Rinse with water and dry thoroughly before painting.

Brush application: Undiluted ALLY-CLEAN 67 may be applied by brush to rust spots and surfaces, which cannot be immersed. Allow about 20 minutes to act before washing off. Dry thoroughly before painting.

05/14 JCG