

Martindale Industrial Estate Hawks Green Lane Cannock Staffs WS11 7XN

> Tel No: 01543 462000 Fax No: 01543 579311

Email: sales@surechemicals.co.uk Web: www.surechemicals.co.uk

Technical Information

Product Code A016

## **ACRYLIC BLOCK SEAL**

Acrylic Block Seal is a specially formulated, quick drying acrylic sealant for concrete and block paving. Developed to resist oil and petroleum contaminants, it also prevents the ingress of water and helps stop the growth of moss and weeds. The sealant will also bind sand and blocks together to prevent 'movement' in block paving.

DURABLE FINISH
PROTECTS SURFACES
QUICK DRYING
EASY TO APPLY

## **DIRECTIONS FOR USE**

Ensure all surfaces are thoroughly dry and free from dirt, grease, oil and any other contaminants. Apply by brush, roller or low pressure sprayer ensuring an even application. Several coats may be applied to achieve the desired finish, allowing approximately 1 hour between applications. Drying times depend on several factors including temperature and thickness of coating. In favourable conditions surfaces should be dry enough for foot traffic after 10 hours and after 24 hours for vehicular traffic. Coverage rates are dependant upon substrate porosity and can vary greatly. For guidance only, one litre of product will cover between 3 and 5 square metres. Tools and equipment may be cleaned with xylene after use.

12/13 SP