



Sure Chemicals Ltd

A solution for every problem

Martindale Industrial Estate
Hawks Green Lane
Cannock
Staffs
WS11 7XN

Tel No: 01543 462000

Fax No: 01543 579311

Email: sales@surechemicals.co.uk

Web: www.surechemicals.co.uk

Technical Information

Product Code L003

LOTOXSOLV

LOTOXSOLV is a high purity, low odour, hydrocarbon solvent that is effective for the cold cleaning and degreasing of a wide range of electronic components and engineering equipment. It is a suitable alternative for those applications where highly volatile or aggressive solvents may not be used. Removes oils, grease, temporary rust preventatives, flux, hydraulic fluids, etc.

LOW TOXICITY, LOW ODOUR

HIGH FLASHPOINT (60° C)

NEGLECTIBLE RESIDUAL DEPOSITS

DIRECTIONS FOR USE

DO NOT heat LOTOXSOLV.

LOTOXSOLV may be applied by dipping, brushing, wiping or low pressure spray.

SOAK TANKS: Small components may be cleaned by immersion and agitation in a bath of LOTOXSOLV, preferably using a basket to contain the parts. For heavily contaminated parts a two-tank process will be most effective. Remove the heavy contamination in the first bath, and rinse in a second bath to remove the remaining residue. Drain excess LOTOXSOLV back into the tank, and allow the parts to air dry. The LOTOXSOLV in the final rinse tank should be replaced when the contamination level becomes unacceptable.

DEGREASING BY HAND: LOTOXSOLV may be sprayed, using a low pressure hand sprayer, or may be brushed or wiped onto the surface of the parts. Always work over a drip tray to catch the excess liquid. Allow parts to air dry or wipe with clean dry rags. Replace rags frequently and safely dispose of dirty rags.

Avoid prolonged contact with skin and ensure adequate ventilation.

05/14 JCG