

Martindale Industrial Estate Hawks Green Lane Cannock Staffs WS11 7XN

Tel No: 01543 462000 Fax No: 01543 579311 Email: sales@surechemicals.co.uk Web: www.surechemicals.co.uk

Technical Information Product Code S0140 SPRAY WASH POWDER (BUPI POWDER)

SPRAY WASH POWDER is a medium duty degreaser for use in hot water spray washing machines. It is suitable for use on most metals including diecast zinc and aluminium alloys, but may dull the surface of highly polished aluminium.

SPRAY WASH POWDER contains a corrosion inhibitor to prevent 'flash rusting' and provide temporary corrosion protection of ferrous metals.

SPRAY WASH POWDER is a blend of mild alkalis, water softeners and surface active agents in a convenient powdered form.

- ECONOMICAL GENERAL PURPOSE DEGREASER
- FAST PENETRATION AND GOOD RINSING
- LOW FOAMING EXCELLENT WETTING
- CONTAINS CORROSION INHIBITORS

DIRECTIONS FOR USE

Use SPRAY WASH POWDER at the rate of 0.25% - 1.0% in water at an operating temperature of 70-85° C (160-180 F).

NOTE: Foaming can occur at temperatures below 70° C (160 F), particularly if pump pressure is high and especially in soft water conditions. Keep concentration down to a minimum and make frequent small additions rather than start off at higher concentration, 0.25% is frequently adequate.

Dulling of the surface may occur with some highly polished aluminium alloys, especially at higher concentrations. Reduce temperature and contact time to minimise the effect. Rinse thoroughly with clean water after treatment.

The amount of corrosion protection provided will depend on the conditions of use, and should be established by practical trials.

05/14 JCG